

Commercial Dehumidifiers



Specifications

MADE IN TAIWAN

Model			PDA-K09M	PDA-K16M
Dehumidify Capacity (Remark 2)		L / hr	9.0	16.0
Power Supply			3ph , 380V , 50Hz	
Electric Characteristics	Total Power Consumption	kW	2.65	4.47
	Total Current	A	4.8	8.1
	Starting Current	A	40	56
Compressor	Type		SCROLL	
	Quantity		1	1
	Power Output	kW	2.11	3.54
Blower	Fan Quantity		1	1
	Air Flow Rate	CMM	28	57
	Extenal Static Pressure	Pa	0	0
	Power Output	kW	0.110	0.200
Protection Devices			High-low pressure switch, compressor internal thermostat, high temp. protection switch, de-ice protection, reverse phase protection	
Pipe Size	Cooling Water Out/Inlet	B	1	1
	Drain (condenser)	B	3/4	3/4
Dimensions	Height	mm	1700	1850
	Width	mm	720	980
	Depth	mm	400	500
Net Weight		Kg	140	200

Remarks:

1. The electric power supply must be in compliant with this table for each model. Any damage or failure caused by using power supply other than specified in this table is not covered in the warranty.
2. The dehumidify capacity and electric characteristics are tested under the conditions: intake air temperature 30℃ DB, relative humidity 80%RH.
3. For the continuous development, the specifications are subjected to modification without notice. The specification is in compliance with the product plate if the content and data altered. If you have any special requirment, please inform us before placing order.

TECO Electric & Machinery Co., Ltd.

Commercial Air Conditioning System Business Division

Address : 10F, No.3-1,Yuan Cyu St.,Nan-Kang,Taipei 115, Taiwan

TEL : 886-2-6615-9111 EXT : 1333

FAX : 886-2-6615-9018

E-mail : aircon@teco.com.tw

Distributor :